



Hole Chart			
Hole	Size		Used For:
	H.M. Door	Wood Door	
A	1-1/8 (29) Dia.	1-1/8 (29) Dia.	Lever/Knob
B	1-1/4 (32) Dia.	1-1/4 (32) Dia.	Cylinder
C	3/4 (19) Dia.	3/4 (19) Dia.	Thumbturn or Emergency Key
D	3/4 (19) Dia.	3/4 (19) Dia.	Visual Indicator / Hotel Indicator
G	1/2 (13) Dia.	1/2 (13) Dia.	Escutcheon Plate Thru Bolts

- Notes:
1. All dimensions given in inches (mm).
 2. Do Not Scale.



**All Series Mortise Locks
Wood and H.M. Door Preparation
Thru Bolted Escutcheon Plate Trim**



TEMPLATE NUMBER	SHEET	DATE
7086-1201	1 of 2	07-15

Lock Function						Holes in Door	
4600	8600	8700	8800			Outside	Inside
4601	8601	8701 8770DT 8771DT 8772DT	8801 8870DT 8871DT 8872DT	838A & B		A, G	A, G
4680	8680	8780	8880				
4681	8681	8781	8881				
4684	8684	8784 836A & B 838A & B	8884 8885 836A & B				
4602	8602	8702	8802	8862			
4605	8605	8705	8805			A, B, G	A, G
4607	8607	8707	8807				
4608	8608	8708	8808				
4624	8624		8824				
		8731	8831				
4690	8690	8790	8890			A, B*, G	A, B*, G
4691	8691	8791	8891				
4660-2	8660-2	8717-2 8730-2 8760-2	8808-2 8811-2 8812-2	8830-2 8860-2 8894-2	8897-2 8898-2 8899-2	A, B, G	A, B, G
4694-2	8694-2	8794-2	8817-2	8895-2			
4695-2	8695-2	8795-2	8818-2	8896-2			
4620	8620	8720 8727	8820 8827				
4622	8622	8722	8809	8860	8898	A, B, G	A, C, G
4632	8632	8732	8822	8861	8899		
	8647	8747	8832	8867			
4660	8660	8760	8840	8896			
4667	8667	8767	8847	8897			
			8833				
			8833-2	8814-2		B, G	A, G
			8813-2			B, G	B, G
			8834	8834-2		B, G	A, B, G
			8813	8815		B, G	C, G
			8864			A, B, C, G	A, C, G

* Lock can be mounted with cylinder outside or inside.
Check for proper application.



**TRADEMARK
HARDWARE**
WORLD OF QUALITY HARDWARE
WWW.TMHARDWARE.COM

**All Series Mortise Locks
Wood and H.M. Door Preparation
Thru Bolted Escutcheon Plate Trim**



1-800-438-1951
www.yalelocks.com

TEMPLATE NUMBER	SHEET	DATE
7086-1201	2 of 2	07-15