


FG3000S90 Fire Glazing Tape in 60- and 90-Minute Wood Doors

Metal Vision Frame Applications


- Verify all applications with your door and/or frame manufacturer
- For exterior fire-rated applications, a clear silicone caulk is recommended for water proofing

FG3000S90

AVAILABLE LENGTHS: 8', 16'




HSS2000




HSS2000 is required to be installed with FG3000S90 for positive pressure applications only. For more information about HSS2000, please see the Adhesive Gasketing section.

Sectional View of Applications




Technical Data For 60- And 90-Minute Wood Doors Equipped With FG3000S90 & HSS2000 (Metal Vision Frame, Single And Multiple Lite Applications)


Lite Configurations



Single Vision Lite, 60-Minute Door



Multiple Vision Lites, 60-Minute Door



Single Vision Lite, 90-Minute Door

The maximum visible glass area allowed for 60-minute single lites is 12" wide x 80" high or 960 square inches per vision lite; 90-minute doors are allowed a maximum visible glass area of 12" wide x 46" high or 552 square inches per vision lite. Multiple lites (allowed on 60-minute doors only) have a maximum combined visible glass area of 1,920 square inches per door.

Lite Specifications

Maximum Dimensions (Single Lite, 60-Minute): 12" wide x 80" high; 960 square inches per lite

Maximum Dimensions (Single Lite, 90-Minute): 12" wide x 46" high; 552 square inches per lite

Maximum Combined Dimensions (Multiple Lites, 60-Minute): Multiple vision lites are allowed in 60-minute doors only; the combined total visible glass area allowed is 1,920 square inches per door

Door Specification

Maximum Dimensions: For both 60- and 90-minute doors, the maximum wood door size is 48" x 96" single, pairs approved

Listing/Labeling Specifications

- Door must be manufactured by companies that are classified by **Underwriters Laboratories Inc.®** for the manufacturing and labeling of hollow metal fire doors. **Warnock Hersey (I.T.S.)** listings are also available through participating hollow metal manufacturers.
- Listed Glazing Products include:
 - **Wire Glazing:** Pilkington, Asahi and Central Glass
- Individual door and frame manufacturers' modification procedures may vary slightly from the size listings shown
- **HSS2000** is required on Positive Pressure applications only

