



FlexTread Anti-Slip Safety Rolls

Preparation and Installation Guide

SURFACE PREPARATION

FLEX-TRED can be quickly applied to most surfaces that are clean, dry, smooth. Surface must be free of moisture, dust, dirt, body oils, grease, wax and soap or detergent films for proper adhesion. Loose scale, rust, paint, concrete or dirt must be removed from surface by wire brushing, sanding, sandblasting or other means.

CLEANING INSTRUCTIONS

WOOSTER FLOOR PREP: An effective alkaline cleaning compound recommended for cleaning all types of interior and exterior surfaces, prior to installing FLEX-TRED. Follow manufacturer's instructions and precautions carefully. (Be sure to rinse thoroughly with clean water!!)

OTHER COMMERCIAL CLEANERS: Cleaners such as those based on butyl cellosolve (with proper ventilation) or non-phosphate alkaline compounds strong enough to emulsify the various contaminants, can be used to clean the mounting surface. Follow manufacturer's instructions according to type of cleaner used.

TEST FOR CLEAN SURFACE: Put a few drops of water on the cleaned surface. If the water forms droplets or beads up, repeat the procedure. When the water spreads out and wets the surface easily, the surface is clean enough to apply FLEX-TRED.

INSTALLATION INSTRUCTIONS

INSTALLATION: After determining that the surface is clean, smooth, and dry, slowly remove the release paper from the underside of the FLEX-TRED safety tread to expose the pressure-sensitive adhesive. Being certain that the FLEX-TRED is in the proper alignment, use foot pressure, roller, or soft rubber mallet to bond the safety tread in place.

TEMPERATURE: Be sure substrate temperature is above 50°F.

APPLICATION TO WOOD: New wood should be sealed or painted prior to application of FLEX-TRED. Loose paint should be removed from old painted surfaces. FLEX-TRED WILL NOT BOND TO WOOD SURFACES TREATED WITH PENTA, CREOSOTE OR OTHER WOOD PRESERVATIVES UNLESS THE WOOD HAS BEEN EXPOSED TO THE ELEMENTS FOR 1 YEAR OR MORE.

APPLICATION TO METAL: Best adhesion is obtained when FLEX-TRED is applied to painted or primed surfaces. Loose scale, paint or rust should be removed prior to painting or priming old or new surfaces.

APPLICATION TO SMOOTH CONCRETE, MARBLE, TILE, TERRAZZO, ETC.: Clean thoroughly with commercial vacuum cleaner to remove dust and dirt. Clean, if necessary, as outlined above. NOTE; FLEX-TRED IS NOT RECOMMENDED FOR USE OVER ROUGH OR BROOM FINISHED CONCRETE.

EDGE SEALER: If the FLEX-TRED safety treads will be exposed to unusually heavy wear or excessive amounts of water, cleaning solutions, oils, grease, gasoline, or other solvents, use FLEX-TRED EDGE SEALER on all exposed edges.

READY TO USE: FLEX-TRED can be walked on immediately. Maximum bond of the adhesive occurs about 24 hours after installation.

IMPORTANT NOTICE TO PURCHASER: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE: Purchase or use of this product constitutes an agreement with Seller and Manufacturer that, if the product proves to be defective or in any way unsuitable, Seller's and Manufacturer's limit of liability for all damages, including but not limited to incidental or consequential damages, and User's or Purchaser's exclusive remedy, regardless of legal theory, including theories of breach of warranty, negligence and strict liability, shall be to receive, at Seller's or Manufacturer's option, repair of the defective product, an equivalent quantity of replacement product or a refund of the purchase price.