



4700LN Series

ANSI/BHMA Grade 1 Certified
Cylindrical Lever Locks



An ASSA ABLOY Group brand



**TRADEMARK
HARDWARE**
WORLD OF QUALITY HARDWARE
WWW.TMHARDWARE.COM

ASSA ABLOY



Table of Contents

CONTENTS

Features3

Finishes & How To Order4

Lever Trim5

Functions 6-8

Electrified Options9

Electrified Accessories.....10

Cylinders11

Cylinders/Keying.....12

Latchbolts13

Strikes.....14

4700LN SERIES CYLINDRICAL LEVER LOCKS

Yale® 4700LN cylindrical locks are the ideal choice for a wide variety of commercial applications where consistent quality, ease of use and installation are required at an economical price. The 4700LN Series is certified to ANSI/BHMA Grade 1 standards and is UL fire-listed for all functions ensuring reliability and peace of mind.



Features

FEATURES

- Available in 19 functions, 3 lever designs, and 9 finishes
- Knurled lever designs available
- Freewheeling trim
- Available with Microshield® antimicrobial coating



SPECIFICATIONS

Door Thickness:	1-3/4" (44mm) to 2" (51mm); 1-3/8" (35mm) or 2-1/4" (57mm), please specify on order
Strike:	ANSI 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center. See page 14 for optional strikes.
Backset:	2-3/4" (70mm)
Handing:	Non-handed
Installation:	ANSI/BHMA A156.115(-W)
ANSI/BHMA:	Certified ANSI/BHMA A156.2, Series 4000 Grade 1
Warranty:	5 year

APPLICATIONS AND LISTINGS

- UL – cUL listed for use on fire doors having a rating up to and including 3 hours
- Windstorm certified refer to local codes  Hurricane
- Meets accessibility guidelines for the Americans with Disabilities Act and the requirements of the Uniform Federal Accessibility Standards and ANSI 117.1

Note: Any retrofit or other field modification to a fire-rated opening can potentially impact the fire-rating of the opening, and Yale Locks & Hardware makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.





Finishes

ANSI/BHMA Code Finish Description			
605 Bright Brass, Clear Coated	606 ¹ Satin Brass, Clear Coated	612 Satin Bronze, Clear Coated	613E Dark Oxidized Satin Bronze - equivalent
			
625 Bright Chrome Plated	626 ^{1,2} Satin Chrome Plated 	BSP Black Suede Powder Coat	WSP White Suede Powder Coat
			

1. Cylinders provided in these finishes only.

2. Available with MicroShield®.

Note: Dark Oxidized Satin Bronze, Oil Rubbed (613) and Black Oxidized Bronze, Oil Rubbed (722) finishes are available by Special Product Application Request only. Contact customer service for more information.



MicroShield®

As part of their promise to provide innovative solutions to their customers, certain ASSA ABLOY Group brands offer the MicroShield® technology, a silver-based antimicrobial coating designed to inhibit the growth of bacteria.

MicroShield® is a registered trademark of Yale Security Inc., an ASSA ABLOY Group company.

HOW TO ORDER

Trim Design	Function	Hand	Latch	Strike	Cylinder	Door Thickness	Finish
See page 8	See pages 5-7	See page 3	See page 13	See page 14	See pages 11-12	See page 3	See page 4


ORDERING EXAMPLE

Trim Design	Function	Hand	Latch	Strike	Cylinder	Door Thickness	Finish
AU	4707LN	RH	694	497	1803-47L	1-3/4"	626

Lever Trim


AUGUSTA AU

Lever: Cast Zinc
Rose: Wrought Brass




MONROE MO

Lever: Cast Zinc
Rose: Wrought Brass



PACIFIC BEACH PB

Lever: Cast Zinc
Rose: Wrought Brass











 Available with large and small format interchangeable core. See page 11-12 for details.

Dimensions shown are in inches (mm).











Functions

4701LN (F75) Passage or Closet Latch • For doors that do not require locking. • Either lever operates latchbolt at all times.  Outside Inside	4702LN (F76A) Privacy, Bedroom or Bath Lock • For lavatory or other privacy doors. • Either lever operates latchbolt unless outside lever is locked by pushbutton inside.* • Button automatically releases when inside lever is turned or door is closed. • Emergency key inserted and turned in hole in outside lever will unlock door from outside. (Emergency key furnished with lockset. P/N 14-5302-1053-048) • Inside lever always active.  Outside Inside	4703LN (F77A) Patio or Privacy Lock • For exit doors with limited entry. • Deadlocking latchbolt. • Either lever operates latchbolt unless outside lever is locked by pushbutton inside.* • Button automatically releases when inside lever is turned or door is closed. • Inside lever always active.  Outside Inside	4704LN (F82A) Entry Lock • For entrance or office doors. • Deadlocking latchbolt. • Either lever operates latchbolt (except when outside lever is locked from inside).* • Pushing button in inside lever locks outside lever. (Automatically releases when inside lever is turned or key is rotated in locked outside lever.) • Latchbolt is operated by key in outside lever or by rotating inside lever. • Inside lever always active.  Outside Inside
4705LN (F86) Storeroom or Closet Lock • For use on storeroom, utility, exit doors. • Deadlocking latchbolt. • Latchbolt operated by lever inside, key in outside lever. • Outside lever always locked.* • Inside lever always active.  Outside Inside	4706LN (F92) Service Station Lock • Deadlocking latchbolt. • Either lever operates latchbolt. • Pushbutton in inside lever locks outside lever. (Automatically releases when inside lever is turned, door is closed or key is rotated in outside lever, except when slotted pushbutton is rotated 90° clockwise to retain outside lever in locked position.)* • Latchbolt operated by key in outside lever, inside lever always active.  Outside Inside	4707LN (F109) Entry Lock • For entrance, general home or office doors. • Deadlocking latchbolt. • Either lever operates latchbolt (except when outside lever is locked from inside).* • Pushing turn button in inside lever locks outside lever. (Automatically releases when inside lever is turned or key is rotated in locked outside lever.) • Outside lever may be retained in locked position by pushing and rotating turn button 90° clockwise to a horizontal position; not released until turn button is manually returned to the vertical position. • Latchbolt is operated by key in outside lever or by rotating inside lever. • Inside lever always active.  Outside Inside	4708LN (F84) Classroom Lock • For classroom or utility room doors. • Deadlocking latchbolt. • Either lever operates latchbolt (except when outside lever is locked by key).* • Inside lever always active. • Key releases outside lever.  Outside Inside

* Lever handles are Free-Wheeling in locked position. Shaded area denotes FreeWheeling lever.



Functions

4709LN (F89) Exit Latch - For exit doors with no-entry desired. - Deadlocking latchbolt. - Outside lever always locked.* - Inside lever always active.  Outside Inside	4718LN (F110) Intruder Classroom Lock - For classroom doors. - Deadlocking latchbolt. - Either lever operates latchbolt (except when outside lever is locked by key from either side). - Outside lever remains locked upon egress - Inside lever always active. (NOTE: Not available with I.C. core cylinders.)  Outside Inside	4721LN (F80) Communicating Lock - For communicating or store entrance doors. - Deadlocking latchbolt. - Either lever operates latchbolt (except when key in either lever locks or unlocks the lever independently of the other).* - Should be used only in offices or rooms with multiple entries. (NOTE: Not available with I.C. core cylinders.)  Outside Inside	4722LN (F90) Corridor Lock - Deadlocking latchbolt. - Either lever operates latchbolt (except when outside lever is locked by inside push-button or key in outside lever). Inside lever always active. - When locked by button, the button automatically releases when inside lever is turned or door is closed. - When locked by key, the automatic release is made inoperative and must be manually unlocked by key.  Outside Inside
4725LN Privacy Lock - For lavatory or other privacy doors. - Either lever operates latchbolt (except when outside lever is locked by inside pushbutton).* - Button automatically releases by turning inside lever or closing door. - Door can be unlocked, when necessary, by operating outside turnbutton. - No emergency key required. - Optional flush turnbutton available for outside. Specify option "FTB".  Outside Inside	4728LN (F111) Communicating Passage Lock - For twin communicating or exit doors where one side operation is required. - Also when space is limited between door and switch panel. - Deadlocking latchbolt. - One lever operation. - Blank rose. - Should be used only where rooms have more than one entrance.  Outside Inside	4729LN (F113) Communicating Classroom Lock - For twin communicating or closet doors where one side operation is required or space between doors is limited. - Deadlocking latchbolt. - Inside lever operates latchbolt except when lever is locked by key.* - Blank rose. - Should be used only where rooms have more than one entrance. (NOTE: Not available with I.C. core cylinders)  Outside Inside	4730LN Utility, Asylum or Institutional Lock - Deadlocking latchbolt. - Latchbolt operated by key in lever from either side. - Both levers always locked.* Note: Not available with IC core cylinders.  Outside Inside

* Lever handles are Free-Wheeling in locked position. Shaded area denotes FreeWheeling lever.



Functions

4739LN (F112)	4755LN	4755LN-D
Communicating Storeroom Lock • For twin communicating or closet doors where one side operation is required or space between doors is limited. • Deadlocking latchbolt. • Latchbolt operated by key only in inside lever. • Inside lever always locked.* • Blank rose. • Should be used only where rooms have more than one entrance. (Note: Not available with I.C. core cylinders)  Outside Inside	Single Dummy Trim • For non-operational levers used for decorative trim. • Rigid lever.  Outside Inside	Double Dummy Trim • For non-operational lever used for decorative trim. • Through-bolted.  Outside Inside

* Lever handles are Free-Wheeling in locked position. Shaded area denotes FreeWheeling lever.



Electrified Options

OPERATION

Electric locks provide the ability to electrically lock or unlock the outside trim from a remote location. Fail Safe locks are commonly used in stair towers to release upon fire alarm activation. Fail Secure locks are used on perimeter doors or security doors to allow ingress using access control technologies (proximity cards, keypads, etc.)



FEATURES

- Free Wheeling lever mechanism.
- Self-contained, continuous-duty integral solenoid (allows installation in standard cylindrical prep).
- Available Fail Safe or Fail Secure.
- Available in 12 or 24 volts DC.
- External rectifier available upon request for AC operation.
- Mechanical cylinder override.
- All 4700LN cylinder options.
- Certified ANSI/BHMA Grade 1. 
- UL listed.
- 1-year limited warranty.


ELECTRICAL SPECIFICATIONS

- Continuous duty solenoid
150 mA @ 24VDC
300 mA @ 12VDC





ELECTROLYNX®

Yale® electrified 4700LN locks are equipped with ElectroLynx connectors. As a standard feature, these connectors link power from the incoming source to electrified locking products, including hinges, locks, exit devices, magnetic holders and strikes.

Note: Electrified door hardware with *ElectroLynx* connectors requires a compatible number of lead wires attached to the door hinge.



FUNCTIONS

Outside	Inside	Function	Function Description	Outside	Inside	Function	Function Description
		4790LN	Fail Safe • Power on locks outside lever. • Inside lever always active. • Latchbolt retracted by key when locked electrically. • Free Wheeling lever when locked electrically.			4780LN	Fail Safe • Power on locks outside lever. • Inside lever always active. • Latchbolt retracted either side except when outside lever is locked electrically. • Free Wheeling lever when locked electrically.
		4791LN	Fail Secure • Power on unlocks outside lever. • Inside lever always active. • Latchbolt retracted by key when power is off. • Free Wheeling lever when power is off (locked).			4781LN	Fail Secure • Power on unlocks outside lever. • Inside lever always active. • Latchbolt retracted either side when power is off. • Free Wheeling lever when power is off (locked).



Electrified Options

BPS POWER SUPPLIES BY SECURITRON®

Operation

Power supplies are designed to provide reliable filtered and regulated power for long life to a variety of electrified hardware components.

Product Features

- Individual output circuit breakers
- Regulated and filtered fuse protected outputs
- LEDs monitor zone status (voltage or no voltage)
- Slide switches connect or disconnect load from power (Not available on 1 Amp supplies)
- Internal Back-Up battery charging circuit
- Rugged steel enclosure
- Fire alarm interface

Listings

- UL CLASS 2

Applications (use with):

- Fail Safe cylindrical locks
- Fail Secure cylindrical locks

Ordering

Ex: BPS-24-4, BPS-12-3

Model	Input	Output	Application
BPS-24-1	120 VAC	1 Amp @ 24 VDC	2-4700LN
BPS-24-2	120 VAC	2 Amp @ 24 VDC	5-4700LN
BPS-24-4	120 VAC	4 Amp @ 24 VDC	11-4700LN
BPS-12-1	120 VAC	1 Amp @ 12 VDC	1-4700LN
BPS-12-3	120 VAC	2 Amp @ 12 VDC	3-4700LN

Consult factory for additional power supply applications.

Yale recommends McKinney®, Pemko and Securitron® for power transfer devices and other electronic accessories.

SECURITRON POWERJUMP™ ICPT

The Securitron PowerJump ICPT Inductive Coupling Power Transfer delivers power contactlessly and invisibly between the frame and door to power electrified hardware on the door. The PowerJump can be installed at the latch side or hinge side of the door and transfers up to 6 watts of power without pins or wires across the door gap, eliminating points of vulnerability and wear ... and no need to core drill the door. The PowerJump is field selectable for 12VDC or 24VDC systems and is ideal for fail secure applications. The unit can hold electrified latches open in continuous duty or can momentarily energize the lockset for latch retraction.



Additional information regarding this product can be found at www.securitron.com.



Cylinders


CYLINDER OPTIONS

The following selection guide indicates the correct cylinder for each locking segment.

Lockset Series:		Types of Cylinder Mechanisms					
4700LN		Conventional		Protected Keyway		Security	
Cylinder Types	Fixed Core	6-pin	7-pin	6-pin	7-pin	6-pin	7-pin
	Key-In-Lever	1803-47L ¹	N/A	K402 ²	N/A	5803-47L ¹	N/A
	Interchangeable Core						
	LFIC	1210	N/A	K800	N/A	5210	N/A
	SFIC	A600	A600	K600	K600	N/A	N/A


Refer to Yale® KeyMark® and/or Cylinders and Keys Catalog sections for all details and how-to-order examples.

1. Cylinders require cylinder sleeve P/N 14-1803-9001-999
2. Cylinder requires cylinder sleeve P/N 14-5305-9078-999



YALE® KEYMARK®


For those applications requiring protected key control, Yale® KeyMark® cylinders guard against unauthorized key duplication. The Yale KeyMark Security Leg® keyway feature increases resistance against picking and impressioning and can easily retrofit into existing systems. For further details and availability, refer to the separate Yale KeyMark catalog.



SECURITY CYLINDERS

Security cylinders contain two independent locking mechanisms. The first is a traditional 6-pin tumbler mechanism with spool drivers for greatly increased picking resistance.

The second is an innovative 5-tumbler rotating disc mechanism with sidebar engagement. The rotating discs are spring loaded and block the bottom of the keyway.




108S SCHLAGE® CYLINDER ADAPTER KIT

Kit used to modify Schlage® cylinder for fit in the 4700LN.

P/N 14-5305-0090-048 - 108S


Kit includes tailpiece and sleeve. To order the 108S adapter kit, use an "S" prefix (i.e., S-AU4707LN).





Cylinders/Keying

OTHER MANUFACTURER KEYWAY CYLINDER/CORES

Illustration	Type	Lever	Number of Pins
	Best® Keyway Core. Available keyed random, master keyed or uncombined. Specify keyway A, B, C, D, E, F, G, H, J, K, L or M.	A600	6 or 7 (Specify)
	Schlage® C Keyway Cylinder. Available 0-bitted or keyed random.	2803-47L x C	6
	Corbin Russwin L4 Keyway Cylinder. Available keyed random.	3803-47L x L4	6
	Corbin 60 Keyway Cylinder. Available keyed random.	3803-47L x 60	6
	Russwin D1 Keyway Cylinder. Available keyed random.	3803-47L x D1	6
	Sargent® LA Keyway Cylinder. Available keyed random.	3803-47L x LA	6
	Schlage® E Keyway Cylinder. Available keyed random.	3803-47L x E	6

Notes: The 2803 and 3803 cylinders require a cylinder sleeve (P/N 14-1803-9001-999) to fit the 4700LN lockset.

LEVERS ACCEPTING SFIC AND OTHER MANUFACTURERS' LARGE FORMAT INTERCHANGEABLE CORES

Illustration	Cylinder Type	Prefix	Number of Pins
	SFIC (Accepts all Small Format Interchangeable Cores)	B (i.e. B-AU, B-MO, B-PB)	6 or 7
	Medeco®, ASSA® (LFIC)	M* (i.e. M-AU)	6
	Schlage® (LFIC)	SI (i.e. SI-AU, SI-PB)	6

*Medeco®, ASSA® option available only with AU lever. (Note: For Medeco 32 series cores.)


LFIC = Large Format Interchangeable Core

SFIC = Small Format Interchangeable Core

Latchbolts

PLAIN LATCHBOLTS

Model No. 693 supplied standard with all 4700LN series locksets without locking function. Standard plain latchbolt has a 2-1/4" (57mm) x 1-1/8" (29mm) beveled front with a 2-3/4" (70mm) backset and a 1/2" (13mm) bolt throw. Optional latchbolts with a greater backset/throw available to special order.




Model No.	Front	Backset	Throw	Front Width	Latch Diameter
693	Beveled	2-3/4" (70mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
F693	Flat	2-3/4" (70mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
3693	Beveled	3-3/4" (95mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)

Note: for 3/4" throw applications, only deadlocking latchbolts available.

DEADLOCKING LATCHBOLTS

Deadlocking latchbolt Model No. 694 supplied standard with all 4700(LN) series locksets with locking function. Standard deadlocking latchbolt has a 2-1/4" (57mm) x 1-1/8" (29mm) beveled front with a 2-3/4" (70mm) backset and a 1/2" (13mm) bolt throw. Optional latchbolts with a greater backset/throw available to special order.



Model No.	Front	Backset	Throw	Front Width	Latch Diameter
694	Beveled	2-3/4" (70mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
F694	Flat	2-3/4" (70mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
3694	Beveled	3-3/4" (95mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
480B	Beveled	2-3/4" (70mm)	3/4" (19mm)	1-1/8" (29mm)	1" (25mm)
F480B	Flat	2-3/4" (70mm)	3/4" (19mm)	1-1/8" (29mm)	1" (25mm)
3480B	Beveled	3-3/4" (95mm)	3/4" (19mm)	1-1/8" (29mm)	1" (25mm)


Note: For 2-3/8" backset, contact Customer Support.

BACKSET EXTENSION LINKS

All 4700LN Series locksets are supplied with standard latchbolts of 2-3/4" (70mm) backset; optional latchbolts with a 3-3/4" (95mm) backset are available to special order for lever locksets only. Extension links are also available for attachment to 2-3/4" (70mm) or 3-3/4" (95mm) backset latchbolts to extend the backset to the desired length.

Desired Backset	Latchbolt Backset	Order Extension List No.
5" (127mm)	2-3/4" (70mm)	481DL
6" (152mm)	3-3/4" (95mm)	481
7" (178mm)	2-3/4" (70mm)	482
8" (203mm)	3-3/4" (95mm)	482
18" (46cm)	2-3/4" (70mm)	484
19" (48cm)	3-3/4" (95mm)	484

Other extension links up to 42" (1.06m) backset are available to special order.



ATTACHING SCREWS

(Not regularly supplied when latchbolts ordered separately).

• For all latchbolts

- #8-32 x 3/4" (19mm) Phillips flat head combination wood and machine screws
- Brass - P/N 81-2022-0416*
- Bronze - P/N 81-2032-0416*

*Specify finish required.


• Hollow Metal Doors

- #8 - 32 x 1" (25mm) Phillips flat head machine screw
- Brass - P/N 81-0022-0420*
- Bronze - P/N 81-0032-0420*




Strikes

Yale® 4700LN locks are available with a variety of strike options. All strikes are located on the same vertical and horizontal center lines as the latchbolt. Some strikes are available in a variety of lip lengths to accommodate varying thickness of doors and frames. To determine the proper length of the lip, measure from the center line of the strike to the edge of the jamb, accounting for any interfering trim (i.e. wood molding) and then add 1/4" (6mm) for curved lip. All strikes are reversible. Strikes are fabricated of either brass, bronze or stainless steel, depending on the lockset trim finish. When ordering strikes separately, specify the finish required.




Model No. 497 ANSI Strike (Standard)

For door and frames with ANSI/BHMA A156.115 preparations. 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center supplied standard. 1-1/8", 1-1/2", and 1-3/4" lip lengths available by special order. Available with optional 202 Strike Box. Specify 497 x 202.



Model No. 371 T-Strike (Optional)

2-3/4" x 1-1/8" x 1-1/4" (70mm x 29mm x 32mm) lip to center available as an option. 1", 1-1/2", 1-3/4" and 2" curved lip lengths available by special order. Wrought strike box supplied.



Model No. 202 Strike Box (Optional)

Available to special order. Specify 497 x 202.

ATTACHING SCREWS

(Not regularly supplied when strikes ordered separately).

For Model No. 497

#12-24 x 1" Phillips flat head combination wood and machine screws.
P/N 81-2012-0620

For Model No. 371

#8-32 x 3/4" (19mm) Phillips flat head combination wood and machine screws.
P/N 81-2012-0416



Notes

Contact Us

The world's favorite lock



U.S.A.

Yale Locks & Hardware

Address: 225 Episcopal Road
Berlin, CT 06037-4004
Tel: 1-800-438-1951
Fax: 1-800-338-0965
yalelocks.com

Canada:

ASSA ABLOY Door Security Solutions Canada

Address: 160 Four Valley Drive
Vaughan, Ontario L4K 4T9
Tel: 1-800-461-3007
Fax: 1-800-461-8989
assaabloydss.ca

International:

ASSA ABLOY Americas International

Tel: 1-905-821-7775
Fax: 1-905-821-1429
assaabloyai.com

Yale Commercial is a business associated with ASSA ABLOY Access and Egress Hardware Group, Inc., an ASSA ABLOY Group company. Copyright © 2010-2019, ASSA ABLOY Access and Egress Hardware Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Access and Egress Hardware Group, Inc. is prohibited. Patent pending and/or patent www.assaabloydss.com/patents.

YALE, with its unique global reach and range of products, is the world's favorite lock.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

42702-5/19

An ASSA ABLOY Group brand

ASSA ABLOY