



# TRADEMARK HARDWARE

WORLD OF QUALITY HARDWARE

## 3400 Series Knob

Grade 1 Cylindrical Knob

### Applications:

- Extra Heavy-Duty Commercial - Industrial - Institutional
- Standard Door Prep - 2 1/8" Diameter (Cross Bore)
- Latch Hole - 1" Diameter (Edge Bore)



### PRODUCT SPECIFICATIONS

#### CERTIFICATIONS:

- BHMA Certified ANSI A156.2, Series 4000, Grade 1
- ANSI A250.13 Severe Windstorm Resistant Component
- UL/cUL Listed for all functions up to 3 hours for "A" label single doors
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated

#### KNOB DIAMETER:

- 2-9/32" (58 mm)

#### ROSE DIAMETER:

- 3" (76 mm)

#### EXPOSED TRIM:

- Wrought Brass or Stainless Steel

#### LOCK CHASSIS:

- Heavy gauge steel, zinc dichromated for corrosion resistance

#### KEYS:

- Two brass keys per lock

#### CYLINDERS:

- Brass 6-pin - Keyed Different - C Keyway
- Other keying options available from factory

#### DOOR THICKNESS:

- 1 3/8" - 1 3/4"

#### BACKSET:

- 2 3/4"
- 2 3/8" Optional

#### LATCHBOLT:

- 1/2" Throw - Stainless Steel
- 2 1/4" x 1 1/8" Faceplate
- Deadlocking latchbolt prevents manipulation when door is closed; keyed functions only

#### STRIKES:

- ANSI 4-7/8" x 1-1/4" strike - standard
- Optional strikes available

#### FINISHES:

- US3, US32D

#### FUNCTIONS:

- 10 - Passage, 17 - Dummy, 40 - Privacy, 50 - Office, 53 - Entry, 70 - Classroom, 80 - Storeroom



www.tmhardware.com



845-388-1300



845-388-1388



sales@tmhardware.com